

AXXAIR



ORBITALNO REZANJE

Tip	Premer (mm)	Debelina (mm)	Teža (kg)	Motor
CC81	5 – 78	0,5 - 7	15	MD21
CC121ECO	5 – 121	0,5 – 7	36	MD21
CC121	5 – 121	0,7 – 15	37	FS25 - FS29 – MOPD
CC171	16 – 170	0,7 – 15	44	FS25 - FS29 - MS18B – MOPD
CC221	59 – 225	1 – 15	51	FS25 - FS29 – MOPD
CC321	140 – 330	1,5 – 15	73	FS25 - FS29 - MS18B - MOPD
CC421	212 – 422	1,5 – 15	176	MS18B - MOPD
CC521	312 – 522	1,5 – 15	200	MS18B - MOPD
CC721	447 – 725	1,5 – 15	245	MS18B - MOPD
CC1100	711 - 1016	1,5 – 15	900	MOPD



ORBITALNO POSNEMANJE FAZ

Tip	Premer (mm)	Debelina (mm)	Teža (kg)	Motor
GA121	15 – 121	Max 8 mm *	37	GA10
GA171	33– 170	Max 8 mm *	44	GA10
GA221	59 – 225	Max 8 mm *	51	GA10
GA321	140– 330	Max 8 mm *	73	GA10
GAP121	15 – 121	Max 12,7 mm	43	GA15
GAP171	22– 170	Max 12,7 mm	50	GA15
GAP221	29 – 225	Max 12,7 mm	57	GA15
GAP321	140– 330	Max 12,7 mm	79	GA15
GAP421	212 – 422	Max 12,7 mm	192	GA15
GAP521	312- 522	Max 12,7 mm	216	GA15
GAP721	447 - 725	Max 12,7 mm	261	GA15



* Odvisno od rezkalne glave

ORBITALNO VARJENJE

Tip	Premer (mm)	Hlajenje	Teža (kg)	AVC/OSC/FIL opcije
SP121	12 – 121	Zračno ali vodno	45	Opcijsko (vodno)
SP171	16 – 170	Zračno ali vodno	52	Opcijsko (vodno)
SP221	59 – 225	Vodno	59	Opcijsko
SP321	140 – 330	Vodno	81	Opcijsko



INLINE VARJENJE



Tip	Premer (mm)	Hlajenje	Teža (kg)
SATF-40ND	6 – 40	Vodno	8,8
SATF-65ND	6 – 65	Vodno	9,2
SATF-115ND	25 – 115	Vodno	9,9
SATP-80	10 – 80	Vodno	7,5

SATF serijsko brez vpenjalnih čeljusti : SMN-xxx



Tip	Premer (mm)	Hlajenje	Teža (kg)
SATO-80M	10 – 80	Zračno	3
SATO-115NDA	19 – 115	Vodno	7,5
SATO-170NDA	25 – 170	Vodno	9
SATO-220NDA	38 – 220	Vodno	11
SATO-115NAOA	19– 115	Vodno	8,8
SATO-170NAOA	25– 170	Vodno	10
SATO-220NAOA	38 – 220	Vodno	13



Tip	El.napetost	Tok	Touch Screen	Verzije
SASL-160	230 V AC	165 A	Da	TRA - T - TF
SASL-161	115 V AC	110 A	Da	TRA - T - TF
SASL-300	400V TRI	300 A	Da	E - EF - T - TF - TOAF



Tip	Premer (mm)	Zunanja faza	Teža (kg)	El.napeteost
DC25 P2	3–25,4	-	2,8	Baterijski polnilec 220 V
DC65-G2	3–63,5	Da	7,1	Baterijski polnilec 220 V
DCPACK-G	3–63,5	Da	7,1	Baterijski polnilec 220 V
DC25-Mx	3–25,4	-	4	220V – 110V
DC65-Mx	3–63,5	Da	8,1	220V – 110V
DCPACK-Mx	3–63,5	Da	8,1	220V – 110V

*M1 :110V - M2 : 220V

“ FACING “
STROJI

AXXAIR FRANCE
HEAD QUARTERS - SIEGE SOCIAL
26800 Etoile sur Rhône
Tél : (33) 4 75 57 50 70
commerce@axxair.com
www.axxair.com



Online katalog



Klasand d.o.o.
Račka cesta 17
2312 Orehova vas
SLOVENIA

Tel: 00386 2 60 40 111
Fax: 00386 2 60 40 110

info@klasand.si
www.klasand.si

Global Process



GLOBAL PROCESS

